

		NovoDisplay DK650
<b>DISPLAY</b>	Technology	IPS Panel, Backlit LED
	Panel Size	65"
	Brightness	350 Nits
	Native Resolution	4K-UHD (3840 x 2160)
	Aspect Ratio	16:9
	Contrast Ratio	1,300:1
	Viewing Angle (Horizontal/Vertical)	178°/178°
	Refresh Rate	60 Hz
	Color Processing	1.07 Billions
	Orientation	Landscape
<b>SYSTEM</b>	Operation System	Android™ v7.1
	CPU	RK3399 ARM Cortex A72 and Quad Core ARM Cortex A53
	GPU	Mali™- T860MP4
	RAM	2GB DDR3
<b>CONNECTIVITY</b>	Internal Storage	16GB (eMMC Flash)
	BYOD Supported System	Windows 7 / 8 / 10 (32 bits and 64 bits), macOS 10.7 and above, Ubuntu, iOS 7.0 and above, Android 4.0 and above, Chromebook
	Input	HDMI v2.0 (x2), DisplayPort v1.2 (x1), DVI-D (x1), VGA (x1), Audio-In Mini-Jack 3.5mm (x1), USB A 2.0 (x3), USB C (x1), microSD Slot, RS232 (x2)
	Output	DVI-D (x1), Audio-Out Mini-Jack 3.5mm (x2), RS232 (x1)
<b>FEATURES</b>	Network	LAN (x1), Wifi 802.11ac,b/g/n 2.4GHz & 5GHz
	Collaboration	BYOD Wireless Screen Mirroring, Meeting ID, Customizable Meeting Room Name, QR Code Connection Support, Split Screen, Moderator, Customizable Welcome Screen, USB Multimedia Reader
<b>GENERAL</b>	Digital Signage Announcement Board	NovoDS Digital Signage - Message and Announcement Board, Intuitive Drag-and-Drop Interface, Flexible Playlist Creation, Dynamic Content from text, audio, photos and videos to webpages, Twitter, RSS, Google Calendar, Weather, and More
	Internal Speakers	8W (x2) (Stereo)
	Power	Supply: AC 100-240V, 50/60Hz. Consumption: 170W, <0.5W (Standby)
	Operation Environment	Operating Temperature: 0°C - 40°C. Operating Humidity: 20% - 85% (No Condensation)
	Storage Environment	Storage Temperature: -10°C - 60°C. Storage Humidity: 10% - 90% (No Condensation)
	VESA	VESA 600 x 400
	Product Dimensions (L x H x W)	1,477 x 852 x 80 mm
	Bezel Width (U / B / L / R)	23,1 mm
	Weight (Net)	29 Kg
	What's Included	Flat Panel, OPS Module, Antennas, Wall Mount Kit, AC Power Cord, Remote Control with Batteries, Document Kit
<b>LOGISTICS</b>	Optional Accessory	LauncherPlus Type A, LauncherPlus Type C, LauncherOne
	Weight (Gross)	40 Kg
	Carton Dimensions (L x W x H)	1,660 x 245 x 1,045 mm
	UPC	813097024671

